

## ESTES ENGINE CHART

- Delays have a tolerance of plus or minus 10% or 1 second, whichever is greater.
- All Estes engines come complete with igniters and patented igniter plugs (Pat. No. 5,410,966 and 5,509,354). The Estes Igniter Plug makes engine ignition extremely reliable.
- Do not fly a rocket/engine combination whose lift-off weight exceeds the recommended maximum lift-off weight.

Prod. No.	Engine Type	Total Impulse	Time Delay	Max. Lift Wt.		Max. Thrust		Thrust Duration	Initial Weight		Propellant Weight	
		N-sec	Sec.	Oz.	g	Newtons	Lbs.	Sec.	Oz.	g	Oz.	g
<b>SINGLE STAGE ENGINES (GREEN LABEL)</b>												
1502	1/4A3-3T	0.625	3	1.0	28	4.9	1.1	0.25	0.20	5.6	0.03	0.85
1503	1/2A3-2T	1.25	2	2.0	57	8.3	1.9	0.3	0.20	5.6	0.06	1.75
1507	A3-4T	2.50	4	2.0	57	6.8	1.5	0.6	0.27	7.6	0.12	3.50
1511	A10-3T	2.50	3	3.0	85	13.0	2.9	0.8	0.28	7.9	0.13	3.78
1593	1/2A6-2	1.25	2	2.0	57	8.9	2.0	0.3	0.53	15.0	0.06	1.56
1598	A8-3	2.50	3	3.0	85	10.7	2.4	0.5	0.57	16.2	0.11	3.12
1601	B4-2	5.00	2	4.0	113	13.2	3.0	1.1	0.70	19.8	0.29	8.33
1602	B4-4	5.00	4	3.5	99	13.2	3.0	1.1	0.74	21.0	0.29	8.33
1605	B6-2	5.00	2	4.5	127	12.1	2.7	0.8	0.68	19.3	0.22	6.24
1606	B6-4	5.00	4	4.0	113	12.1	2.7	0.8	0.71	20.1	0.22	6.24
1613	C6-3	10.00	3	4.0	113	15.3	3.4	1.6	0.88	24.9	0.44	12.48
1614	C6-5	10.00	5	4.0	113	15.3	3.4	1.6	0.91	25.8	0.44	12.48
1622	C11-3	10.00	3	6.0	170	22.1	4.9	0.8	1.14	32.2	0.39	11.00
1623	C11-5	10.00	5	5.0	142	22.1	4.9	0.8	1.18	33.3	0.39	11.00
1666	D12-3	20.00	3	14.0	396	32.9	7.4	1.6	1.49	42.2	0.88	24.93
1667	D12-5	20.00	5	10.0	283	32.9	7.4	1.6	1.52	43.1	0.88	24.93
1673	E9-4	30.00	4	15.0	425	25.0	5.6	2.8	2.00	56.7	1.27	35.80
1674	E9-6	30.00	6	12.0	340	25.0	5.6	2.8	2.00	56.7	1.27	35.80
<b>UPPER STAGE ENGINES (PURPLE LABEL)</b>												
1504	1/2A3-4T	1.25	4	1.0	28	8.3	1.9	0.3	0.21	6.0	0.06	1.75
1599	A8-5	2.50	5	2.0	57	13.3	3.0	0.5	0.62	17.6	0.11	3.12
1607	B6-6	5.00	6	2.5	71	12.1	2.7	0.8	0.78	22.1	0.22	6.24
1615	C6-7	10.00	7	2.5	71	15.3	3.4	1.6	0.95	26.9	0.44	12.48
1624	C11-7	10.00	7	4.0	113	22.1	4.9	0.8	1.22	34.5	0.39	11.00
1668	D12-7	20.00	7	8.0	226	32.9	7.4	1.6	1.55	44.0	0.88	24.93
1675	E9-8	30.00	8	10.0	283	25.0	5.6	2.8	2.00	56.7	1.2	35.80
<b>BOOSTER STAGE ENGINES (RED LABEL)</b>												
1608	B6-0	5.00	None	4.0	113	12.1	2.7	0.8	0.58	16.4	0.22	6.24
1616	C6-0	10.00	None	4.0	113	15.3	3.4	1.6	0.80	22.7	0.44	12.48
1621	C11-0	10.00	None	6.0	170	22.1	4.9	0.8	0.98	27.8	0.39	11.00
1665	D12-0	20.00	None	14.0	396	32.9	7.4	1.6	1.44	40.9	0.88	24.93
<b>PLUGGED ENGINES - FOR USE WITH R/C ROCKET GLIDERS (BLUE LABEL)</b>												
1669	D11-P	20.00	None	16.0	453	27.6	6.2	1.8	1.55	44.0	0.88	24.93
1676	E9-P	30.00	None	15.0	425	25.0	5.6	2.8	2.0	56.	1.27	35.80

The data listed above is from randomly chosen production samples.  
NOTE: The "T" designates a mini-engine.